


# **DEZZI D2500 MEGA MOVER**





Designed & Manufactured in South Africa



# **DEZZI D2500 MEGA MOVER**

# **SPECIFICATION SHEET**

\*Desmond Equipment SA (Pty) Ltd reserves the right to modify specifications without notice.

#### **ENGINE**

TYPE: Cummins

MODEL: 6BT - 5.9 Turbocharged

CAPACITY: 5.9 Litres

POWER: 123kW @ 2500 RPM
TORQUE: 640Nm @ 1500 RPM
APPROXIMATE FUEL BURN:
10-12 Ltrs/Hr - Heavy Cycle

8-10 Ltrs/Hr - Light Cycle

#### **TRANSMISSION**

TYPE: ZF MODEL: 4WG160

• 4 Speed automatic shift transmission with modulated directional

clutch

· Driven via converter from engine

• Operation by a single lever on left of steering wheel MAXIMUM SPEED IN GEARS: 4 Forward - 3 Reverse

	FIRST	SECOND	IHTKD	FOURTH
FORWARD (km/h)	7.6	13.9	26.0	43.0
REVERSE (km/h)	8.0	14.6	28.0	-

## **AXLES**

TYPE: ZF

MODEL: MT-L 3105

Front axle fixed, rear axle oscillates through 12°

Double reduction drives with standard differentials driving all

four wheels

# **TYRES**

STANDARD TYRES: 600/65 R26

#### **BRAKES**

#### SERVICE BRAKE

- · Sealed outboard wet disc brakes
- · Fully hydraulically activated
- Brakes are activated by use of one brake pedal

**PARK BRAKE** 

- Spring applied hydraulic release fail-safe
- Operator engages manually

# **STEERING**

- · Centre pivot frame articulation
- Fully hydraulic powered with flow controlling system
- Full flow filtering
- Steering angle 40° in each direction

## STEERING HYDRAULICS

- Two 76.2 mm bore x 472 mm stroke double acting cylinders
- Orbital controlled
- Working pressure 2400 Psi

#### **ELECTRICS**

VOLTAGE: 24 Volt
BATTERY: 2 x 12 Volt
ALTERNATOR: 24 Volt / 70 Amp

# **CAB**

- Fully adjustable weight compensation swivel seat with seat belt
- ROPS and FOPS certified
   V
- Windscreen wiper
- Fully enclosed and lockable
   Improved operator visibility
- Rotating orange beacon light Front & rear night working lights

# **SERVICE CAPACITIES**

COOLING SYSTEM: 32 Litres (50% anti-freeze)

**ENGINE CRANKCASE:** 16 Litres

DIFFERENTIALS: 28 Litres (per differential)

TRANSMISSION: 26 Litres
DIESEL TANK: 240 Litres

HYDRAULIC SYSTEM: 185 Litres (Tank Only) 210 Litres (Total System)

PLANETARY HUB: 6 Litres (per planetary)

# **OPERATIONAL WEIGHTS**

**OPERATING WEIGHT: 14 500 kg** 

TURNING CIRCLE: 6 470mm radius outside wheel

#### LOADER

- Log Lift Mesera 83F Crane (Grab size 0.65 Slew 270 degrees)
- Improved slew damping system on grab for better control

## LOADER HYDRAULICS

- Closed system with pressure control
- Fixed displacement gear type pump
- Full flow filtering

# **PUSH PILER**

- Hydraulically operated from cab
- Free-floating design
- 4 Fully adjustable tynes

