



DEZZI KATO HD308 US-R5 EXCAVATOR



BUILT AFRICA TOUGH

machinesales@dezzi.co.za

www.dezzi.co.za



DEZZI KATO HD308 US-R5 EXCAVATOR

SPECIFICATION SHEET

*Desmond Equipment SA (Pty) Ltd reserves the right to modify specifications without notice.

ENGINE

TYPE : Yanmar (four stroke cycle)
 MODEL : 4TNV98-ZCVK-BHC
 DISPLACEMENT : 3.32 Ltr
 POWER : 57Hp (42.6KW) @ 2 100RPM (ISO Net)
 TORQUE : 236Nm @ 1 575RPM (ISO Net)

TRAVEL SYSTEM

- Drive - Independent axial piston motor with reduction for each side
- Brakes - Independent disk parking brake for each side applied automatically when the travel levers are in neutral position
- Lubrication - Sealed for life rollers and front idlers with floating seals

CAB & CONTROLS

- All weather sound suppressed cab on 4 point viscous mounting
- Right-hand lever controls the boom and bucket
- Inner right hand lever (with foot pedal) controls the right-hand track
- Inner left hand lever (with foot pedal) controls the left hand track
- Left hand lever controls the arm and swing
- Pilot control - travel, boom, arm, bucket and swing
- Engine throttle - Electric "Accell Dial"
- Meter & Gauges - Operation mode, engine rpm, warning lights
- Work lights provided on the left side of boom and right side of front cover

HYDRAULIC SYSTEM

- Double variable piston pump and gear pump
- 5 + 5 section multiple control valves (with one free service circuit)
- Maximum discharge flow 2x 74L/min
- Maximum discharge pressure 29.4MPa
- Maximum discharge pressure (high power) 31.4MPa

SERVICE CAPACITIES

COOLING SYSTEM : 15.3 Liters
 ENGINE OIL : 11.6 Liters
 HYDRAULIC TANK : 50.9 Liters
 HYDRAULIC SYSTEM : 103 Liters
 FUEL TANK : 130 Liters
 TRACK DRIVES : 2 x 1.3 Liters

OPERATIONAL WEIGHTS

OPERATING WEIGHTS : 8 300kg
 GROUND PRESSURE : 43kPa


BUCKET ATTACHMENT

BUCKET CAPACITY : 0.3 m3
 BUCKET WIDTH (no side-cutters) 702mm
 BUCKET WIDTH (with side-cutters) 816mm
 BUCKET TEETH : 4


RANGES

ARM RANGE (standard arm 1 620mm)	
*A Maximum digging radius	6 470mm
*B Maximum digging depth	4 120mm
*C Maximum digging height	7 430mm
*D Maximum vertical wall	3 620mm
*E Maximum dumping height	5 320mm
*F Minimum swing radius	1 630mm

Operational Ranges



Dimensions - HD308US-R5



Machine Width - 2 300mm

BUILT AFRICA TOUGH



CALL : 0800 DEZZI / 33994

Head Office: +27 (0)39-685 4100

Email: machinesales@dezzi.co.za

www.dezzi.co.za